



UNCOMPROMISING IN EVERY SENSE™



## iC7FX

### 7" SURROUND EFFECTS CEILING-MOUNT LOUDSPEAKER

Surround Effects Ceiling-Mount Loudspeakers for multi-channel home theater applications. Designed for use with iC7500, iC7600, iC8500, and iC8600 left/center/right loudspeakers.

#### KEY FEATURES

- **Integrated Woofer/Baffle Design** Delivers improved low frequency response by employing a larger woofer cone than competitive models of the same diameter.
- **Proprietary Bridge-Mounted Tweeter Adjustment Mechanism** Directs the high frequency sounds to the listening area in any direction up to 20° without diffraction.
- **Weather-Resistant Construction** Enables installation in moist environments such as bathrooms, kitchens, saunas, and outdoor areas under eaves
- **Install With Confidence** The best-built loudspeakers deserve the best protection—the ICS Lifetime Limited Warranty.

**iC7FX****7" SURROUND EFFECTS CEILING-MOUNT LOUDSPEAKER****iC7FX****7" SURROUND EFFECTS  
LOUDSPEAKER**

FG01641

Packaged Individually with Round MicroThin™ Grille

**RELATED PRODUCTS**

**CM700 BKT New**  
Construction Bracket  
FG01308



**CM700 Hole Cover**  
FG01309



**CE6 Metal Loudspeaker**  
Enclosure  
FG00944

**FEATURES**

- Integrated baffle/frame assembly increases the cone area for deeper bass than competitive speakers of the same diameter
- 7" injection-molded TCC™ (Talc, Carbon, and Ceramic-filled) woofer cone with butyl rubber surround for deep, low distortion bass response
- Dual pivoting 1" fluid-cooled Teteron® dome tweeters provide ultra-wide dispersion and smooth response
- Bridge-mounted surround effects (FX) array directs sound at opposing angles for realistic surround sound effects
- Dipole/Bipole switch enables optimum room matching
- Paintable, flush-mount MicroPerf™ aluminum grille
- Weather-resistant construction enables installation in wet environments and outdoors

**SPECIFICATIONS**


- Recommended amplifier power: 10 - 150 watts
- Impedance: 8 ohm nominal; 6 ohm minimum
- Frequency response: 55 Hz to 21 kHz +/- 3 dB

**DIMENSIONS**

- Frame dimensions (with grille): 9-1/4" (23.5 cm) diameter
- Hole cutout dimensions: 8" (20.3 cm) diameter
- Depth behind ceiling (5/8" drywall): 4-3/8" (11 cm)

**WARRANTY**

- Lifetime Limited

E N G I N E E R E D B Y  **NILES®**

©2010 Niles Audio Corporation. All Rights Reserved. Niles, the Niles logo and Blending High Fidelity and Architecture are registered trademarks of Niles Audio Corporation. All other trademarks are the property of their respective owners. CS0310A