

IntelliControl[®]ICS

INTEGRATED CONTROL SOLUTIONS

DATA SHEET



MODULAR MULTIZONE RECEIVER

GXR2

GXR2

MODULAR MULTI-ZONE RECEIVER

FG01174

FEATURES

- **Modular MultiZone Receiver** distributes up to six sources to six zones
- **Built-in High Current 12-channel Amplifier** delivers 55 watts per channel RMS @ 8 ohms and 85 watts per channel @ 4 ohms to each of six zones
- **Integrated Six Slot Card Cage** accepts any combination of up to six IntelliControl ICS integration modules
- **Plug and Play Integration** of TM-AM/FM, TM-XM, TM-Sirius and IM-iPod ICS integration modules
- **Reliable "One Touch to Music"** operation using IntelliControl ICS Touch Screens, Keypads and remote controls
- **Party Mode** turns on all your favorite areas from any keypad or remote control
- **Global Off** turns off all areas from any keypad or remote control
- **Tone Controls** fine tune bass and treble in each separate zone
- **Balance Control** fine tunes channel levels in each separate zone
- **Programmable Turn-On Volume** for each zone
- **Alarm Clock and Sleep Timer** for each zone
- **Paging/Doorbell Input** enables system wide voice announcements from a phone system or doorbell sounds from the Niles DBI-1
- **Zone Linking** allows a grouping of zones to be controlled as a single zone. Turn-On, Source selection, Paging and Turn-Off all work in unison, yet each zone has independent volume adjustment and muting
- **Home Theater Integration Ports** enable audio and video source components shared with the home theater system to be turned on, controlled via IR and turned off as needed



NILES®

- **Selectable Fixed/Variable Zone Preamp Outputs** with 12 Volt Triggers for external amplifier applications
- **Source Matching Gain Control** ensures changing sources doesn't require changing volume control settings
- **Removable Speaker Connectors** hold up to 12-gauge speaker wire
- **Expandable up to 30 Zones** with additional GXR2s
- Includes Rack Mount Kit and hardware

SPECIFICATIONS

- Agency certifications: Class 2/SELV covering US, Canadian and EU markets
- 55 watts x 12 channels
- Frequency response: 26-20 kHz +/- 3 db
- Signal to Noise: > = 85 db
- Power supply: AC 120V, 60Hz
- Power consumption: 1500 watts maximum

DIMENSIONS

- 17-3/8" wide x 5-3/4" high (including feet) x 18" deep

WARRANTY AND SHIPPING

- Warranty: Two year limited
- Shipping: Weight: 54 lbs

